

Model #4173/5173(H) - Awning Energy Ratings

Glass Options	Glazing	Gas	Grille	Energy Star Zone(s)		ER	SHGC	VT	CR	U-Value (Metric)	U-Value Imp (Imperial)	R-Value (Imperial)
				Canada	US							
366 (2)	Double			None	NC,SC,S	13	0.18	0.41	55	1.71	0.30	3.33
366 (2)	Double		Y	None	NC,SC,S	12	0.16	0.37	55	1.71	0.30	3.33
366 (2)	Double	Arg/Kry		1	N,NC,SC,S	18	0.18	0.41	59	1.48	0.26	3.85
366 (2)	Double	Arg/Kry	Y	1	N,NC,SC,S	17	0.16	0.37	59	1.48	0.26	3.85
366 (2)	Double	Argon		1	N,NC,SC,S	17	0.18	0.41	59	1.54	0.27	3.70
366 (2)	Double	Argon	Y	1	N,NC,SC,S	16	0.16	0.37	59	1.54	0.27	3.70
Bronze/LOF (3)	Double			None	C	21	0.37	0.37	56	1.82	0.32	3.13
Bronze/LOF (3)	Double		Y	None	C	20	0.34	0.33	56	1.82	0.32	3.13
Bronze-LOF (3)	Double	Arg/Kry		None	NC	24	0.37	0.37	56	1.71	0.30	3.33
Bronze-LOF (3)	Double	Arg/Kry	Y	None	NC	22	0.34	0.33	56	1.71	0.30	3.33
Bronze-LOF (3)	Double	Argon		None	NC	24	0.37	0.37	56	1.71	0.30	3.33
Bronze-LOF (3)	Double	Argon	Y	None	N,NC	22	0.34	0.33	56	1.71	0.30	3.33
Grey-LOF (3)	Double			None	C	20	0.35	0.33	56	1.82	0.32	3.13
Grey-LOF (3)	Double		Y	None	C	18	0.32	0.3	56	1.82	0.32	3.13
Grey-LOF (3)	Double	Arg/Kry		None	NC	23	0.35	0.33	56	1.71	0.30	3.33
Grey-LOF (3)	Double	Arg/Kry	Y	None	NC	21	0.32	0.3	56	1.71	0.30	3.33
Grey-LOF (3)	Double	Argon		None	NC	23	0.35	0.33	56	1.71	0.30	3.33
Grey-LOF (3)	Double	Argon	Y	None	N,NC	21	0.32	0.3	56	1.71	0.30	3.33
LOF (3)	Double			1	None	27	0.46	0.49	56	1.82	0.32	3.13
LOF (3)	Double		Y	None	None	24	0.42	0.44	56	1.82	0.32	3.13
LOF (3)	Double	Arg/Kry		1 2	N	30	0.47	0.49	56	1.71	0.30	3.33
LOF (3)	Double	Arg/Kry	Y	1	N	27	0.42	0.44	56	1.71	0.30	3.33
LOF (3)	Double	Argon		1 2	N	30	0.47	0.49	56	1.71	0.30	3.33
LOF (3)	Double	Argon	Y	1	N	27	0.42	0.44	56	1.71	0.30	3.33
LOF-LOF (2&3)	Double	Arg/Kry		1 2	N	32	0.42	0.46	44	1.48	0.26	3.85
LOF-LOF (2&3)	Double	Arg/Kry	Y	1 2	N,NC	29	0.38	0.41	44	1.48	0.26	3.85
LOF-LOF (2&3)	Double	Argon		1 2	N	32	0.42	0.46	44	1.48	0.26	3.85
LOF-LOF (2&3)	Double	Argon	Y	1 2	N,NC	29	0.38	0.41	44	1.48	0.26	3.85
366 (2)	Triple	Arg/Kry		1 2	N,NC,SC,S	23	0.16	0.37	72	1.19	0.21	4.76
366 (2)	Triple	Arg/Kry	Y	1 2	N,NC,SC,S	22	0.15	0.34	72	1.19	0.21	4.76
366 (2)	Triple	Argon		1 2	N,NC,SC,S	23	0.16	0.37	72	1.19	0.21	4.76
366 (2)	Triple	Argon	Y	1 2	N,NC,SC,S	22	0.15	0.34	72	1.19	0.21	4.76
366 (2)	Triple	Krypton		1 2	N,NC,SC,S	23	0.16	0.37	73	1.19	0.21	4.76
366 (2)	Triple	Krypton	Y	1 2	N,NC,SC,S	22	0.15	0.34	73	1.19	0.21	4.76
Bronze	Triple	Arg/Kry		1	N,NC	26	0.36	0.36	63	1.59	0.28	3.57
Bronze	Triple	Arg/Kry	Y	1	N,NC	23	0.32	0.32	63	1.59	0.28	3.57
Bronze	Triple	Argon		1	N,NC	26	0.36	0.36	63	1.59	0.28	3.57
Bronze	Triple	Argon	Y	1	N,NC	23	0.32	0.32	63	1.59	0.28	3.57
Bronze	Triple	Krypton		1	N,NC	26	0.36	0.36	64	1.59	0.28	3.57
Bronze	Triple	Krypton	Y	1	N,NC	23	0.32	0.32	64	1.59	0.28	3.57
Bronze-LOF (5)	Triple	Arg/Kry		1 2	N,NC	30	0.33	0.33	70	1.31	0.23	4.35
Bronze-LOF (5)	Triple	Arg/Kry	Y	1 2	N,NC,SC	28	0.30	0.3	70	1.31	0.23	4.35
Bronze-LOF (5)	Triple	Argon		1 2	N,NC	30	0.33	0.33	69	1.31	0.23	4.35

Model #4173/5173(H) - Awning Energy Ratings

Glass Options	Glazing	Gas	Grille	Energy Star Zone(s)		ER	SHGC	VT	CR	U-Value (Metric)	U-Value Imp (Imperial)	R-Value (Imperial)
				Canada	US							
Bronze-LOF (5)	Triple	Argon	Y	1 2	N,NC,SC	28	0.30	0.3	69	1.31	0.23	4.35
Bronze-LOF (5)	Triple	Krypton		1 2	N,NC	31	0.33	0.33	70	1.25	0.22	4.55
Bronze-LOF (5)	Triple	Krypton	Y	1 2	N,NC,SC	30	0.30	0.3	70	1.25	0.22	4.55
Bronze-LOF-LOF (3&5)	Triple	Arg/Kry		1 2 3	N,NC	33	0.32	0.31	75	1.14	0.20	5.00
Bronze-LOF-LOF (3&5)	Triple	Arg/Kry	Y	1 2 3	N,NC,SC	32	0.29	0.28	75	1.14	0.20	5.00
Bronze-LOF-LOF (3&5)	Triple	Argon		1 2 3	N,NC	33	0.32	0.31	75	1.14	0.20	5.00
Bronze-LOF-LOF (3&5)	Triple	Argon	Y	1 2 3	N,NC,SC	32	0.29	0.28	75	1.14	0.20	5.00
Bronze-LOF-LOF (3&5)	Triple	Krypton		1 2 3	N,NC	35	0.32	0.31	77	1.08	0.19	5.26
Bronze-LOF-LOF (3&5)	Triple	Krypton	Y	1 2 3	N,NC,SC	33	0.29	0.28	77	1.08	0.19	5.26
Grey	Triple	Arg/Kry		1	N,NC	25	0.34	0.32	63	1.59	0.28	3.57
Grey	Triple	Arg/Kry	Y	1	NC	23	0.31	0.29	63	1.59	0.28	3.57
Grey	Triple	Argon		1	N,NC	25	0.34	0.32	63	1.59	0.28	3.57
Grey	Triple	Argon	Y	1	NC	23	0.31	0.29	63	1.59	0.28	3.57
Grey	Triple	Krypton		1	N,NC	25	0.34	0.32	64	1.59	0.28	3.57
Grey	Triple	Krypton	Y	1	NC	23	0.31	0.29	64	1.59	0.28	3.57
Grey-LOF (5)	Triple	Arg/Kry		1 2	N,NC	29	0.31	0.3	70	1.31	0.23	4.35
Grey-LOF (5)	Triple	Arg/Kry	Y	1 2	N,NC,SC	27	0.28	0.27	70	1.31	0.23	4.35
Grey-LOF (5)	Triple	Argon		1 2	N,NC	29	0.31	0.3	69	1.31	0.23	4.35
Grey-LOF (5)	Triple	Argon	Y	1 2	N,NC,SC	27	0.28	0.27	69	1.31	0.23	4.35
Grey-LOF (5)	Triple	Krypton		1 2	N,NC	30	0.31	0.3	70	1.25	0.22	4.55
Grey-LOF (5)	Triple	Krypton	Y	1 2	N,NC,SC	29	0.28	0.27	70	1.25	0.22	4.55
Grey-LOF-LOF (3&5)	Triple	Arg/Kry		1 2 3	N,NC,SC	32	0.30	0.29	75	1.14	0.20	5.00
Grey-LOF-LOF (3&5)	Triple	Arg/Kry	Y	1 2 3	N,NC,SC,S	30	0.27	0.26	75	1.14	0.20	5.00
Grey-LOF-LOF (3&5)	Triple	Argon		1 2 3	N,NC,SC	32	0.30	0.29	75	1.14	0.20	5.00
Grey-LOF-LOF (3&5)	Triple	Argon	Y	1 2 3	N,NC,SC,S	30	0.27	0.26	75	1.14	0.20	5.00
Grey-LOF-LOF (3&5)	Triple	Krypton		1 2 3	N,NC,SC	33	0.30	0.29	77	1.08	0.19	5.26
Grey-LOF-LOF (3&5)	Triple	Krypton	Y	1 2 3	N,NC,SC,S	32	0.27	0.26	77	1.08	0.19	5.26
LOF (5)	Triple	Arg/Kry		1 2 3	N	35	0.41	0.44	70	1.31	0.23	4.35
LOF (5)	Triple	Arg/Kry	Y	1 2	N,NC	32	0.37	0.4	70	1.31	0.23	4.35
LOF (5)	Triple	Argon		1 2 3	N	35	0.41	0.44	69	1.31	0.23	4.35
LOF (5)	Triple	Argon	Y	1 2	N,NC	32	0.37	0.4	69	1.31	0.23	4.35
LOF (5)	Triple	Krypton		1 2 3	N	36	0.41	0.44	70	1.25	0.22	4.55
LOF (5)	Triple	Krypton	Y	1 2 3	N,NC	34	0.37	0.4	70	1.25	0.22	4.55
LOF-LOF (3&5)	Triple	Arg/Kry		1 2 3	N,NC	38	0.40	0.42	75	1.14	0.20	5.00
LOF-LOF (3&5)	Triple	Arg/Kry	Y	1 2 3	N,NC	36	0.36	0.38	75	1.14	0.20	5.00
LOF-LOF (3&5)	Triple	Argon		1 2 3	N,NC	38	0.40	0.42	75	1.14	0.20	5.00
LOF-LOF (3&5)	Triple	Argon	Y	1 2 3	N,NC	36	0.36	0.38	75	1.14	0.20	5.00
LOF-LOF (3&5)	Triple	Krypton		1 2 3	N,NC	39	0.40	0.42	77	1.08	0.19	5.26
LOF-LOF (3&5)	Triple	Krypton	Y	1 2 3	N,NC	37	0.36	0.38	77	1.08	0.19	5.26

(SHGC) Solar Heat Gain Coefficient: The higher the SHGC, the more solar heat the window allows.

(VT) Visible Transmittance: The higher the VT, the more daylight is allowed in.

(CR) Condensation Resistance: The higher the CR, the less likely condensations is to occur.